

JA10	1 Piece
<p>Elevation</p> <p>Section. a-a</p> <p>plan</p> <p>int.</p> <p>ext.</p>	
LOCATION	Stair Box
DIMENSIONS	Window 1.00x0.60m.
DESCRIPTION	One-sash window opening, made up of 2.8mm thick UPVC/PVC frame and profiles.
MATERIAL	<p>FRAME Movable and fixed frame in PVC and STEEL with a minimum thickness of 2.8mm.</p> <p>GLASS Smoked clear tempered double glass with 6+12+6mm thickness, argon gas inside, UV transmission <20%, heat transfer coefficient Ug 0.60w/m2k.</p>
FINISHING	Smooth finish in white color.
THRESHOLD/SILL	In cement mortar at a line of 1: 2.5 with 30mm thickness, executed on site.
HINGES	According to the specified series.
IRONWARE	<p>LOCK According to the specified series.</p> <p>HANDLES According to the specified series.</p>
OBSERVATIONS	All dimensions must be verified on site.

JAB08	1 Piece						
LOCATION	Secretary						
DIMENSIONS	Window 4.50x1.00m.						
DESCRIPTION	Window opening with two sliding sashes and one fixed sash, made up of 2.8mm thick UPVC/PVC frame and profiles.						
MATERIAL	<table border="1"> <tr> <td>FRAME</td> <td>Movable and fixed frame in PVC and STEEL with a minimum thickness of 2.8mm.</td> </tr> <tr> <td>GLASS</td> <td>Smoked clear tempered double glass with 6+12+6mm thickness, argon gas inside, UV transmission ≤20%, heat transfer coefficient U ≤0.60w/m2k.</td> </tr> </table>	FRAME	Movable and fixed frame in PVC and STEEL with a minimum thickness of 2.8mm.	GLASS	Smoked clear tempered double glass with 6+12+6mm thickness, argon gas inside, UV transmission ≤20%, heat transfer coefficient U ≤0.60w/m2k.		
FRAME	Movable and fixed frame in PVC and STEEL with a minimum thickness of 2.8mm.						
GLASS	Smoked clear tempered double glass with 6+12+6mm thickness, argon gas inside, UV transmission ≤20%, heat transfer coefficient U ≤0.60w/m2k.						
FINISHING	Smooth finish in white color.						
THRESHOLD/BELL	In cement mortar of a line of 1: 2.5 with 30mm thickness, executed on site.						
IRONWARE	<table border="1"> <tr> <td>HINGES</td> <td>According to the specified series.</td> </tr> <tr> <td>LOCK</td> <td>According to the specified series.</td> </tr> <tr> <td>HANDLES</td> <td>According to the specified series.</td> </tr> </table>	HINGES	According to the specified series.	LOCK	According to the specified series.	HANDLES	According to the specified series.
HINGES	According to the specified series.						
LOCK	According to the specified series.						
HANDLES	According to the specified series.						
OBSERVATIONS	All dimensions should be verified on site.						

COLOR	RED	YELLOW	GREEN	CYAN	BLUE
PEN	7	7	7	7	7
WIDTH	0.10	0.35	0.5	0.8	1.20