

 <p>中海油石化工程有限公司 CNOOC Petrochemical Engineering Co.,Ltd.</p>	<p><b>DATA SHEET FOR BOOSTER PUMP (P-282221A/B/C)</b></p>	Owner Doc.No.	CMIT-240048-728-ROT-15.17-0001	
		Job's Doc. No.	253001D0728ME00D01	
		Phase	Detailed Design	
		Rev.	C	Page 1 of 7

Company:  CNOOC IRAQ LIMITED

Project: FQN NEW DEGASSING STATION UPGRADING PROJECT

Unit: FQN DEGASSING STATION

Contract No.: CMIT-PRT-10.53-240048

Discipline: ROT

Prepared by: *Liu H.Q.*

Checked by: *Xie Long*

Approved by: *Huang J.D.*

C	ISSUED FOR APPROVAL	Liu Hanqi	Xie Long	Huang Jingdong		20250925
B	ISSUED FOR APPROVAL	Liu Hanqi	Xie Long	Huang Jingdong		20250907
A	ISSUED FOR REVIEW	Liu Hanqi	Xie Long	Huang Jingdong		20250720
Rev.	Description	Prepared	Checked	Approved		Date

 <p>中海油石化工程有限公司 CNOOC Petrochemical Engineering Co.,Ltd.</p>		<h3 style="text-align: center;">DATA SHEET FOR BOOSTER PUMP (P-282221A/B/C)</h3>						Owner Doc.No.	CMIT-240048-728-ROT-15.17-0001			
								Job's Doc. No.	253001D0728ME00D01			
								Phase	Detailed Design			
								Rev	C	Page 2 of 7		
1	Note	APPLICABLE TO: PURCHASE			APPLICABLE NTL/INTNTL STANDARD:			API610 12th Edition		Rev		
2	FOR:	CNOOC IRAQ LIMITED			MANUFACTURER:			*				
3	SITE:	MISSAN OIL FIELD, MISSAN PROVINCE, IRAQ			TYPE:			CENTRIFUGAL PUMP				
4	UNIT:	FQN DEGASSING STATION	NO. REQ:	3(2W+1S)	MODEL:			*				
5	SERVICE:	BOOSTER PUMPS			NO. STAGES:			*		PUMP SIZE:	*	
6	ITEM NO.:	P-282221A/B/C			PID NO.:			*				
7	LIQUID CHARACTERISTICS											
8		Units	Maximum	Minimum	<b>Note</b>  Max/Min values referenced only to the operating conditions listed herein.	SERVICE :			CONTINUOUS			
9	LIQUID TYPE OR NAME :	Oil and Water										
10	VAPOR PRESSURE :	kPa(a)	1100									
11	RELATIVE DENSITY :		0.95	0.915								
12	SPECIFIC HEAT :	kJ(kg-k)										
13	VISCOSITY :	mPa·s	40	15.2								
14	OPERATING CONDITIONS (6.1.3)											
15		Units	Maximum	Rated	Normal	Minimum	C.L. Impeller					
16	NPSHa Datum:											
17	PUMPING TEMPERATURE :	°C			67~73							
18	FLOW :	m³/hr	135	135								
19	DISCHARGE PRESSURE : (6.3.2)	kPa(g)		2570	2570							
20	SUCTION PRESSURE :	kPa(g)	1054	1044	1044							
21	DIFFERENTIAL PRESSURE :	kPa		1526	1526							
22	DIFFERENTIAL HEAD :	m		170	170							
23	NPSH <sub>A</sub> :	m		5	5							
24	HYDRAULIC POWER :	kW		*								
25	SITE AND UTILITY DATA											
26	LOCATION:				COOLING WATER :			N/A				
27	OUTDOOR	UNHEATED	UNDER ROOF				INLET	RETURN	DESIGN			
28	MOUNTED AT :	GROUND	● TROPICALISATION REQD				TEMP °C	MAX				
29	ELECTRIC AREA CLASSIFICATION: (6.1.22)						PRESS. kPa	MIN				
30	GROUP	IIB	Class II /Group				SOURCE					
31	SITE DATA :											
32	ELEVATION (MSL) :	25	m	BAROMETER : 750.43 mm Hg			COOLING WATER CHLORIDE CONCENTRATION: _____ ppm					
33	RANGE OF AMBIENT TEMPS:MIN / MAX			-5 / 55 °C			INSTRUMENT AIR :				MAX _____ kPa MIN _____ kPa	
34	RELATIVE HUMIDITY: MIN / MAX			25 / 80 %			STEAM					
35	UNUSUAL CONDITIONS:			DUST			TEMP °C	Max	DRIVERS	HEATING		
36	UTILITY CONDITIONS :											
37	ELECTRICITY :	DRIVERS	HEATING	CONTROL	SHUTDOWN	PRESS. kPa	Min					
38	VOLTAGE	400V		230V		Max						
39	PHASE	3		1		Min						
40	HERTZ	50		50								
41	PERFORMANCE											
42	DRIVER (7.1)											
43	PROPOSAL CURVE NO.	*	RPM	*	DRIVER TYPE			MOTOR				
44	As Tested Curve No.			*	GEAR			NO				
45	IMPELLER DIA.: (NOTE13)	RATED	*	MAX.	*	MIN.	*	mm	NO			
46	RATED POWER	*	kW	EFFICIENCY			*	(%)	VARIABLE SPEED REQUIRED			
47	RATED CURVE BEP FLOW (at rated impeller dia) (6.1.16)			*	m³/hr			SOURCE OF VARIABLE SPEED				
48	MIN FLOW :	THERMAL	*	m³/hr	STABLE	*	m³/hr	OTHER				
49	PREFERRED OPERATING REGION (6.1.16)			*	to	*	m³/hr	MANUFACTURER			*	
50	ALLOWABLE OPERATING REGION (6.9.4.1)			*	to	*	m³/hr	NAMEPLATE POWER (7.1.5)			*	
51	MAX HEAD @ RATED IMPELLER			*	m			NOMINAL RPM			*	
52	MAX POWER @ RATED IMPELLER			*	kW			RATED LOAD RPM			*	
53	NPSH3 AT RATED FLOW (6.1.9) :			*	m			FRAME OR MODEL				
54	CENTERLINE OF PUMP TO NPSHA DATUM			*	m			ORIENTATION			HORIZONTAL	
55	NPSH MARGIN AT RATED FLOW (6.1.10) :			*	m			LUBRICATION			GREASE	
56	SPECIFIC SPEED (6.1.17)			m³/hr,m	*			BEARING TYPE : (7.1.9)			Anti-Friction	
57	SUCTION SPECIFIC SPEED LIMIT (6.1.11)			m³/hr,m				RADIAL			*	
58	SUCTION SPECIFIC SPEED (6.1.11)			m³/hr,m	*			THRUST			*	
59	MAX. ALLOW. SOUND PRESSURE LEVEL (6.1.19)			85@1m (dBA)				STARTING METHOD			Closed-Valve (Unloaded) Start	
60	ESTIMATED MAX SOUND PRESSURE LEVEL			(dBA)				DRIVER DATASHEET NUMBER			*	
61	MAX. ALLOWABLE SOUND POWER LEVEL (6.1.19)			*				SERVICE FACTOR / EXPLOSION PROOF:			* / Ex(d) IIB T4	
62	ESTIMATED MAX SOUND POWER LEVEL							DRIVER DESIGN STANDARD			*	
63	ENCLOSURE: IP55 for motor, IP65 for junction box. INSULATION CLASS: F TEMPERATURE RISE: B											
64	* To be filled and confirmed by the Vendor.											

 中海油石化工程有限公司 CNOOC Petrochemical Engineering Co., Ltd.		<b>DATA SHEET FOR BOOSTER PUMP</b> <b>(P-282221A/B/C)</b>				Owner Doc.No.	CMIT-240048-728-ROT-15.17-0001																																																																																								
						Job's Doc. No.	253001D0728ME00D01																																																																																								
						Phase	Detailed Design																																																																																								
						Rev	C	Page 3 of 7																																																																																							
1	Note	CONSTRUCTION						Rev																																																																																							
2	API PUMP TYPE:	OH2 [Based on API 610 definitions]			CASING MOUNTING(6.3.14, 9.3.8.3):			CENTERLINE																																																																																							
3	NOZZLE CONNECTIONS(6.4.2):				CASING TYPE:			MULTIPLE VOLUTE																																																																																							
4	<table border="1"> <tr> <th>Size</th> <th>Facing</th> <th>Rating</th> <th>Position</th> </tr> <tr> <td>VTA</td> <td>RF</td> <td>300</td> <td>END</td> </tr> <tr> <td>DISCHARGE</td> <td>VTA</td> <td>RF</td> <td>300</td> </tr> <tr> <td></td> <td></td> <td></td> <td>TOP</td> </tr> </table>				Size	Facing	Rating	Position	VTA	RF	300	END	DISCHARGE	VTA	RF	300				TOP	OH3 BACK-PULLOUT LIFTING DEVICE REQD. (9.1.2.6)																																																																										
Size	Facing	Rating	Position																																																																																												
VTA	RF	300	END																																																																																												
DISCHARGE	VTA	RF	300																																																																																												
			TOP																																																																																												
5					CASE PRESSURE RATING:																																																																																										
6					MAWP(6.3.6): * bar g			@ DESIGN °C																																																																																							
7					HYDROTEST (8.3.2)(8.3.2.2,5,6,8,11): 1.5*MAWP bar g			@ AMBIENT °C																																																																																							
8	PRESSURE CASING AUX. CONNECTIONS: (6.4.3) (7.6.2.2)				WETTING AGENT REQUIRED FOR HYDROTEST(8.3.2.7):			NO																																																																																							
9	<table border="1"> <tr> <th>No.</th> <th>Size</th> <th>Type</th> <th>Facing</th> <th>Rating</th> <th>Posn.</th> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>VTA</td> <td>*</td> <td>RF</td> <td>300</td> <td>BOTTOM</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </table>				No.	Size	Type	Facing	Rating	Posn.								VTA	*	RF	300	BOTTOM																																											HYDROTEST OH PUMP AS ASSEMBLY (8.3.2.14):			YES																											
No.	Size	Type	Facing	Rating	Posn.																																																																																										
	VTA	*	RF	300	BOTTOM																																																																																										
10					SUCTION PRESS. REGIONS DESIGNED FOR MAWP (6.3.8):			YES																																																																																							
11					ROTOR:																																																																																										
12					SHAFT FLEXIBILITY INDEX (SFI) (9.1.1.3)			YES																																																																																							
13					FIRST CRITICAL SPEED WET (MULTISTAGE PUMPS ONLY)			N / A																																																																																							
14					COMPONENT BALANCE TO ISO 21940-11 G1.0 (6.9.3.4):			G2.5																																																																																							
15					SHRINK-FIT-LIMITED MOVEMENT IMPELLERS (9.2.2.3)			N / A																																																																																							
16					ROTATION (VIEWED FROM COUPLING END):			CCW																																																																																							
17					IMPELLERS INDIVIDUALLY SECURED (6.6.3) :			YES																																																																																							
18																																																																																															
19																																																																																															
20																																																																																															
21																																																																																															
22																																																																																															
23																																																																																															
24																																																																																															
25																																																																																															
26																																																																																															
27																																																																																															
28																																																																																															
29																																																																																															
30																																																																																															
31																																																																																															
32																																																																																															
33																																																																																															
34																																																																																															
35																																																																																															
36																																																																																															
37																																																																																															
38																																																																																															
39																																																																																															
40																																																																																															
41																																																																																															
42																																																																																															
43																																																																																															
44																																																																																															
45																																																																																															
46																																																																																															
47																																																																																															
48																																																																																															
49																																																																																															
50																																																																																															
51																																																																																															
52																																																																																															
53																																																																																															
54																																																																																															
55																																																																																															
56																																																																																															
57																																																																																															
58																																																																																															
59																																																																																															
<b>MATERIAL (6.12.1.1)</b>																																																																																															
<table border="1"> <tr> <td>APPENDIX H CLASS</td> <td colspan="2">D-2</td> </tr> <tr> <td>MINIMUM DESIGN METAL TEMPERATURE (6.12.4.1)</td> <td colspan="2">-5 °C</td> </tr> <tr> <td>MAXIMUM ALLOWABLE TEMPERATURE(3.1.20)</td> <td colspan="2">101 °C</td> </tr> <tr> <td>REDUCED-HARDNESS MATERIALS REQ'D (6.12.1.14)</td> <td colspan="2">YES</td> </tr> <tr> <td>APPLICABLE HARDNESS STANDARD(6.12.1.14)</td> <td colspan="2">MR0175</td> </tr> <tr> <td>BARREL :</td> <td colspan="2">N/A</td> </tr> <tr> <td>CASE :</td> <td colspan="2">ASTM A995 Gr.5A</td> </tr> <tr> <td>DIFFUSERS :</td> <td colspan="2"></td> </tr> <tr> <td>IMPELLER :</td> <td colspan="2">ASTM A890 Gr.5A</td> </tr> <tr> <td>IMPELLER WEAR RING :</td> <td colspan="2">*</td> </tr> <tr> <td>CASE WEAR RING :</td> <td colspan="2">*</td> </tr> <tr> <td>SHAFT:</td> <td colspan="2">ASTM A276 - UNS S32760</td> </tr> <tr> <td>BOWL (IF VS-TYPE)</td> <td colspan="2">N/A</td> </tr> <tr> <td>COUPLING / COUPLING GUARD :</td> <td colspan="2">* / *</td> </tr> <tr> <td>INSPECTION CLASS</td> <td colspan="2">Level 3</td> </tr> </table>									APPENDIX H CLASS	D-2		MINIMUM DESIGN METAL TEMPERATURE (6.12.4.1)	-5 °C		MAXIMUM ALLOWABLE TEMPERATURE(3.1.20)	101 °C		REDUCED-HARDNESS MATERIALS REQ'D (6.12.1.14)	YES		APPLICABLE HARDNESS STANDARD(6.12.1.14)	MR0175		BARREL :	N/A		CASE :	ASTM A995 Gr.5A		DIFFUSERS :			IMPELLER :	ASTM A890 Gr.5A		IMPELLER WEAR RING :	*		CASE WEAR RING :	*		SHAFT:	ASTM A276 - UNS S32760		BOWL (IF VS-TYPE)	N/A		COUPLING / COUPLING GUARD :	* / *		INSPECTION CLASS	Level 3																																											
APPENDIX H CLASS	D-2																																																																																														
MINIMUM DESIGN METAL TEMPERATURE (6.12.4.1)	-5 °C																																																																																														
MAXIMUM ALLOWABLE TEMPERATURE(3.1.20)	101 °C																																																																																														
REDUCED-HARDNESS MATERIALS REQ'D (6.12.1.14)	YES																																																																																														
APPLICABLE HARDNESS STANDARD(6.12.1.14)	MR0175																																																																																														
BARREL :	N/A																																																																																														
CASE :	ASTM A995 Gr.5A																																																																																														
DIFFUSERS :																																																																																															
IMPELLER :	ASTM A890 Gr.5A																																																																																														
IMPELLER WEAR RING :	*																																																																																														
CASE WEAR RING :	*																																																																																														
SHAFT:	ASTM A276 - UNS S32760																																																																																														
BOWL (IF VS-TYPE)	N/A																																																																																														
COUPLING / COUPLING GUARD :	* / *																																																																																														
INSPECTION CLASS	Level 3																																																																																														
<b>BEARINGS AND LUBRICATION (6.10.1)</b>																																																																																															
<table border="1"> <tr> <td>BEARING (TYPE / NUMBER): (6.10.1.1) (6.10.1.11)</td> <td colspan="2"></td> </tr> <tr> <td>RADIAL</td> <td>*</td> <td>/</td> <td>*</td> <td colspan="2"></td> </tr> <tr> <td>THRUST</td> <td>*</td> <td>/</td> <td>*</td> <td colspan="2"></td> </tr> <tr> <td colspan="4">REVIEW AND APPROVE THRUST BEARING SIZE : (9.2.5.2.6)</td> <td colspan="2"></td> </tr> <tr> <td colspan="4">BEARING HOUSING (6.10.2.1,9,12,13,14)</td> <td colspan="2">YES</td> </tr> <tr> <td colspan="4">LUBRICATION (6.11.3) (6.11.4) (9.3.12.4):</td> <td colspan="2">RING OIL</td> </tr> <tr> <td colspan="4">PRESSURE LUBE SYSTEM TO API-614, CHAPTER:</td> <td colspan="2"></td> </tr> <tr> <td colspan="4">API-614 DATA SHEETS ATTACHED (9.2.6.4)</td> <td colspan="2"></td> </tr> <tr> <td colspan="4">PRESSURIZED LUBE OIL SYSTEM MOUNTED ON BASEPLATE:</td> <td colspan="2"></td> </tr> <tr> <td colspan="4">LOCATION OF PRESSURIZED LUBE OIL SYSTEM:</td> <td colspan="2"></td> </tr> <tr> <td colspan="4">INTERCONNECTING PIPING PROVIDED BY</td> <td colspan="2">SUPPLIER</td> </tr> <tr> <td colspan="4">OIL VISC. ISO GRADE</td> <td colspan="2">VG 46</td> </tr> <tr> <td colspan="4">VENT-TO-HOUSING CONSTANT LEVEL OILER(6.10.2.4):</td> <td colspan="2">REQUIRED</td> </tr> <tr> <td colspan="4">OIL MIST PROVISIONS(6.11.3)</td> <td colspan="2">*</td> </tr> <tr> <td colspan="4">GREAE LUBRICATION(6.11.4)</td> <td colspan="2">*</td> </tr> </table>									BEARING (TYPE / NUMBER): (6.10.1.1) (6.10.1.11)			RADIAL	*	/	*			THRUST	*	/	*			REVIEW AND APPROVE THRUST BEARING SIZE : (9.2.5.2.6)						BEARING HOUSING (6.10.2.1,9,12,13,14)				YES		LUBRICATION (6.11.3) (6.11.4) (9.3.12.4):				RING OIL		PRESSURE LUBE SYSTEM TO API-614, CHAPTER:						API-614 DATA SHEETS ATTACHED (9.2.6.4)						PRESSURIZED LUBE OIL SYSTEM MOUNTED ON BASEPLATE:						LOCATION OF PRESSURIZED LUBE OIL SYSTEM:						INTERCONNECTING PIPING PROVIDED BY				SUPPLIER		OIL VISC. ISO GRADE				VG 46		VENT-TO-HOUSING CONSTANT LEVEL OILER(6.10.2.4):				REQUIRED		OIL MIST PROVISIONS(6.11.3)				*		GREAE LUBRICATION(6.11.4)				*	
BEARING (TYPE / NUMBER): (6.10.1.1) (6.10.1.11)																																																																																															
RADIAL	*	/	*																																																																																												
THRUST	*	/	*																																																																																												
REVIEW AND APPROVE THRUST BEARING SIZE : (9.2.5.2.6)																																																																																															
BEARING HOUSING (6.10.2.1,9,12,13,14)				YES																																																																																											
LUBRICATION (6.11.3) (6.11.4) (9.3.12.4):				RING OIL																																																																																											
PRESSURE LUBE SYSTEM TO API-614, CHAPTER:																																																																																															
API-614 DATA SHEETS ATTACHED (9.2.6.4)																																																																																															
PRESSURIZED LUBE OIL SYSTEM MOUNTED ON BASEPLATE:																																																																																															
LOCATION OF PRESSURIZED LUBE OIL SYSTEM:																																																																																															
INTERCONNECTING PIPING PROVIDED BY				SUPPLIER																																																																																											
OIL VISC. ISO GRADE				VG 46																																																																																											
VENT-TO-HOUSING CONSTANT LEVEL OILER(6.10.2.4):				REQUIRED																																																																																											
OIL MIST PROVISIONS(6.11.3)				*																																																																																											
GREAE LUBRICATION(6.11.4)				*																																																																																											
<b>REMARKS :</b> <hr/> <hr/> <hr/> <hr/> <hr/> <hr/>																																																																																															
* To be filled and confirmed by the Vendor.																																																																																															



中海油石化工程有限公司  
CNOOC Petrochemical Engineering Co., Ltd.

## DATA SHEET FOR BOOSTER PUMP (P-282221A/B/C)

Owner Doc.No.	CMIT-240048-728-ROT-15.17-0001	
Job's Doc. No.	253001D0728ME00D01	
Phase	Detailed Design	
Rev	C	Page 4 of 7

1	Note	INSTRUMENTATION	SEAL SUPPORT SYSTEM MOUNTING	Rev
2		INSTRUMENTATION PER API-670 (7.5.2)	SEAL SUPPORT SYSTEM MOUNTED ON PUMP BASEPLATE	
3		ACCELEROMETER (7.5.2.1)	(7.6.1.4)	YES
4		NUMBER OF ACCELEROMETERS		
5		MOUNTING LOCATION OF ACCELEROMETERS	LOCATION ON OR OFF BASEPLATE (7.4.6):	
6			ON BASEPLATE	
7			INTERCONNECTING PIPING BY	VENDOR
8		PROVISION FOR MTG ONLY (6.10.2.13)	MECHANICAL SEAL (6.8.1)	
9		FLAT SURFACE REQUIRED (6.10.2.14)	API 682 DATA SHEET ATTACHED :	VENDOR PROVIDE
10		VIBRATION PROBES (7.5.2.2) (REMARK 6, REMARK 8)	ADDITIONAL CENTRAL FLUSH PORT (6.8.9)	*
11		VIBRATION PROBES REQUIRED (7.5.2.2):	HEATING JACKET REQ'D. (6.8.11)	
12		VTC	FLUSH PLAN (REMARK 2,3,4)	PLAN11+53B
13		NUMBER PER RADIAL BEARING		
14		NUMBER PER AXIAL BEARING	HEATING AND COOLING (6.1.22)	
15		THREADED PROVISION FOR MTG ONLY (6.10.2.13; 6.6.12)	COOLING REQ'D (REMARK 7)	YES
16		FLAT SURFACE PROVISION ONLY (6.10.2.14)	COOLING WATER PIPING PLAN (7.6.3.1) (7.6.3.3)	
17		MONITORS AND CABLES SUPPLIED BY (7.5.2.6)(7.5.2.7)	COOLING WATER PIPING (7.6.2.7)	
18		TEMPERATURE (7.5.2.3) (REMARK 1)	FITTINGS	
19		TEMPERATURE PROBES REQUIRED (7.5.2.3) (7.5.2.5):	COOLING WATER PIPING MATERIALS	
20		VTC	COOLING WATER REQUIREMENTS: SUPPLY PRESSURE	kPag
21		PROVISIONS FOR MOUNTING ONLY (6.10.2.2)	BEARING HOUSING	m³/hr
22		RADIAL BEARING TEMPERATURE :	HEAT EXCHANGER	m³/hr
23		NUMBER PER RADIAL BEARING :	TOTAL COOLING WATER	m³/hr
24		THRUST BEARING TEMPERATURE :	HEATING MEDIUM	
25		NUMBER PER THRUST BEARING ACTIVE SIDE :	OTHER	
26		NUMBER PER THRUST BEARING INACTIVE SIDE :	HEATING PIPING (7.6.2.7)	
27		TEMP. GAUGES (WITH THERMOWELLS) (9.1.3.5)	PIPING & APPURTENANCES (7.6.1.1)(8.3.2.13,15,16)	
28		TEMP. GAUGE LOCATION :	TAG ALL OPICES (7.6.2.4)	YES
29		SUPPLY UPPER/LOWER CASING RTD'S FOR WARMUP	SOCKET WELD UNION ON 1st SEAL GLAND NIPPLE (7.6.2.8)	NO
30		PRESSURE GAUGE TYPE (7.6.2.10)	MANIFOLD AUX PIPING SYSTEMS AT SKID EDGE (7.6.1.6):	
31		PRESSURE GAUGE LOCATION :	VENT : (REMARK 5)	N / A
32			DRAIN :	YES
33		Remarks	COOLING WATER :	*
34		1. In Between Seals, PI and TI shall be established on the Seal Plan Supply and	AUXILIARY SYSTEM MATERIALS (7.6.1.2):	TABLE H.4
35		Return Lines.	THREADED PIPING JOINTS ALLOWED (7.6.2.9):	NO
36		2. The API Seal Code, Seal Drawing, and Seal Manufacturers recommendation for		
37		the selected seal shall be furnished along with the Bid.		
38		3. The Wetted Parts Material of Cartridge Seal shall be compatible with the Pumping		
39		Fluid and the Material of Seal Flush Systems shall be compatible with the Barrier Fluid.		
40		4. In case Plan 53B selected, Nitrogen Charging Kit and Manual Makeup System		
41		(Portable Trolley with Hand Pump) shall be provided by the Vendor.		
42		5. Pump shall be Self-Venting.		
43		6. Probes Provision Supply shall be verified based on the Final Bearing		
44		Selection stated on Page 3 of 6.		
45		7. Fan Cooling should be the 1st choice. If Fan Cooling is inadequate, one of		
46		Annex B Plans shall be selected.		
47		8. If the booster pump provided by the Vendor is equipped with rolling bearings,		
48		an accelerometer must be installed at the bearing housing.		
49				
50				
51				
52				
53				
54				
55				
56				
57				

\* To be filled and confirmed by the Vendor.



中海油石油化工工程有限公司  
CNOOC Petrochemical Engineering Co., Ltd.

**DATA SHEET FOR BOOSTER PUMP**  
**(P-282221A/B/C)**

Owner Doc.No.	CMIT-240048-728-ROT-15.17-0001	
Job's Doc. No.	253001D0728ME00D01	
Phase	Detailed Design	
Rev	C	Page 5 of 7

1	Note	SURFACE PREPARATION, PAINT & SPARES					TEST	Rev
2	MANUFACTURER'S STANDARD (8.4.3.4)	YES					SHOP INSPECTION (8.1.1)	Yes
3	OTHER (SEE BELOW)						PERFORMANCE CURVE & DATA APPROVAL PRIOR TO SHIPMENT (8.3.4.6)	YES
4	SPECIFICATION NO.						TEST WITH SUBSTITUTE SEAL (8.3.3.3.1)	NO
5	PUMP:						MATERIAL CERTIFICATION REQUIRED (6.12.1.8):	YES
6	PUMP SURFACE PREPARATION	REQUIRED					CASING	YES
7	PRIMER	*					IMPELLER	YES
8	FINISH COAT	*					SHAFT	YES
9	BASEPLATE:						OTHER(AUXILIARY PIPING & PIPING COMPONENTS)	YES
10	BASEPLATE SURFACE PREPARATION	REQUIRED					CASTING REPAIR WELD PROCEDURE APPR REQD (6.12.2.5) :	YES
11	PRIMER:	*					INSPECTION REQUIRED FOR CONNECTION WELDS (6.12.3.4)	
12	FINISH COAT	*					MAG PARTICLE	
13	UNDERSIDE	*					RADIOGRAPHY	YES
14	SHIPMENT: (8.4.1)	EXPORT					LIQUID PENETRANT	YES
15	EXPORT BOXING REQUIRED	YES					ULTRASONIC	
16	OUTDOOR STORAGE MORE THAN 12 MONTHS	YES					INSPECTION REQUIRED FOR CASTINGS (8.2.2.3.2) (8.2.2.4)	
17	SPARE ROTOR ASSEMBLY PACKAGED FOR:						MAG PARTICLE	
18	ROTOR STORAGE ORIENTATION (9.2.8.2)						RADIOGRAPHY	YES
19	SHIPPING & STORAGE CONTAINER FOR VERTICAL STORAGE (9.2.8.3)						LIQUID PENETRANT	YES
20	N2 PURGE REQUIRED (9.2.8.4)						ULTRASONIC	
21	SPARE PARTS (L.3.4)						HARDNESS TEST REQUIRED (6.12.1.14; 8.2.2.7)	YES
22	START-UP	YES					ADDNL SUBSURFACE EXAMINATION (6.12.1.6) (8.2.1.3)	YES
23	NORMAL MAINTENANCE	YES					FOR	SHAFT/IMPELLER
24	WEIGHTS kg (7.1.3)						METHOD	ULTRASONIC
25	ITEM No	PUMP	DRIVER	GEAR	BASE	TOTAL	PMI TESTING REQUIRED (8.2.2.8)	YES
26	*	*	*	*	*	*	COMPONENTS TO BE TESTED	
27							ALL PRESSURE BOUNDARY PARTS OF ALLOY MATERIALS	
28	DIMENSION mm						RESIDUAL UNBALANCE TEST (J.4.1.2)	YES
29	L*W*H	*					NOTIFICATION OF SUCCESSFUL PERFORMANCE TEST	
30	COORDINATION MEETING REQUIRED (10.1.3)	YES					(8.1.1.3) (8.3.3.4.6)	YES
31	MAXIMUM DISCHARGE PRESSURE TO INCLUDE (6.3.2)						BASEPLATE (NOZZLE LOAD) TEST (7.4.24)	
32	MAX RELATIVE DENSITY	YES					HYDROSTATIC TEST (8.3.2)	WIT
33	OPERATION TO TRIP SPEED						HYDROSTATIC TEST OF BOWLS & COLUMN (9.3.13.1)	
34	MAX DIA. IMPELLERS AND/OR NO OF STAGES	YES					PERFORMANCE TEST (8.3.3)	WIT
35	CONNECTION DESIGN APPROVAL (9.2.1.4)						TEST IN COMPLIANCE WITH (8.3.3.2)	YES 8.3.3.2
36	TORSIONAL ANALYSIS / REPORT (6.9.2.10)	NO					TEST DATA POINTS TO (8.3.3.4)	YES 8.3.3.4
37	ANNEXURE L REQUIREMENTS	YES					TEST TOLERANCES TO (8.3.3.5)	TABLE 16
38	PROGRESS REPORTS (L.3.3)	YES					ALTERNATE TEST TOLERANCES PER (8.3.3.5)	
39	OUTLINE OF PROCEDURES FOR OPTIONAL TESTS (L.2.5)	YES					NPSH (8.3.4.3)	
40	ADDITIONNAL DATA REQUIRING 20 YEARS RETENTION (8.2.1.1)	YES					NPSH BASED IN 1ST STG ONLY ALLOWED (8.3.4.3.2)	
41	LATERAL ANALYSIS REQUIRED (9.2.4.1.2)						TEST NPSHA LIMITED TO 110% SITE NPSHA (8.3.3.7)	*
42	ROTOR DYNAMIC BALANCE TO 4W/N (6.9.3.5)						RETEST ON SEAL LEAKAGE (8.3.3.3.2)	WIT
43	INSTALLATION LIST IN PROPOSAL (L.2.3.2.1))	YES					RETEST REQUIRED AFTER FINAL HEAD ADJ USTMENT(8.3.3.8.2)	
44	VFD STEADY STATE FORCED RESPONSE ANALYSIS (6.9.2.3)	NO					COMPLETE UNIT TEST (8.3.4.4.1)	WIT
45	TRANSIENT FORCED RESPONSE(6.9.2.4)						_SOUND LEVEL TEST (8.3.4.5)	WIT
46	BEARING LIFE CALCULATIONS REQUIRED (6.10.1.11)	YES					CLEANLINESS PRIOR TO FINAL ASSEMBLY (8.2.2.6)	NON-WIT
47	CASING RETIREMENT THICKNESS DRAWING [L.3.6.1 cc) 7) xiii]						LOCATION OF CLEANLINESS INSPECTION	@ VENDOR'S
48	CONNECTION BOLTING (7.6.1.7)	PTFE COATED					CHECK FOR CO-PLANAR MOUNTING PAD SURFACES (7.4.8)	NON-WIT
49	VENDOR TO KEEP REPAIR AND HT RCDS (8.2.1.1.c)	YES					MECHANICAL RUN TEST UNTIL OIL TEMP STABLE (8.3.4.2.1)	WIT
50	VENDOR SUBMIT TEST PROCEDURES (8.3.1.1)	YES					4 HR. MECH RUN AFTER OIL TEMP STABLE (8.3.4.2.2)	WIT
51	SUBMIT INSPECTION CHECK LIST (8.1.5)	YES					BRG HSG RESONANCE TEST (8.3.4.7)	*
52	ACOUSTIC ANALYSIS OF CROSSOVER PASSAGE (BB3,BB5) (9.2.1.5)	NO					STRUCTURAL RESONANCE TEST (9.3.9.2)	
53	API-691 DOCUMENTATION REQUIRED (6.1.3.1)						REMOVE / INSPECT HYDRODYNAMIC BEARINGS AFTER TEST (9.2.7.4)	
54							AUXILIARY EQUIPMENT TEST (8.3.4.6)	WIT
55							EQUIPMENT TO BE INCLUDED IN AUXILIARY TESTS:	
56							SEAL PLAN 53B WHOLE SYSTEM	
57							LOCATION OF AUXILIARY EQUIPMENT TEST	
58							@ VENDOR'S	
59							IMPACT TEST (6.12.4.3)	PER EN 13445
60							PER ASME SECTION VIII	
61							CASING DISASSEMBLY AFTER TEST (8.3.3.9)	
62							SPARE PARTS TEST (8.3.4.8)	
63								
64								
65								
66								

\* To be filled and confirmed by the Vendor.



## DATA SHEET FOR BOOSTER PUMP (P-282221A/B/C)

Owner Doc.No.	CMIT-240048-728-ROT-15.17-0001	
Job's Doc. No.	253001D0728ME00D01	
Phase	Detailed Design	
Rev	C	Page 6 of 7

1	Note	PRESSURE VESSEL DESIGN CODE REFERENCES		Rev
2		<b>THESE REFERENCES SHALL BE PROVIDED BY THE MANUFACTURER</b>		
3		CASTING FACTORS USED IN DESIGN (PER TABLE 4)		
4		SOURCE OF MATERIAL PROPERTIES (6.3.5)		YES
5		WELDING AND REPAIRS (6.12.3.1)		
6		<b>THESE REFERENCES SHALL BE PROVIDED BY THE PURCHASER. (DEFAULT TO TABLE 11 IF NO PURCHASER PREFERENCE IS STATED)</b>		
7		ALTERNATE WELDING CODES AND STANDARDS:		YES
8		WELDING REQUIREMENT (APPLICABLE CODE OR STANDARD)		DEFAULT PER TABLE 11
9		ALTERNATE WELDER / OPERATOR QUALIFICATION STANDARD :		
10		ALTERNATE WELDING PROCEDURE QUALIFICATION STANDARD :		
11		NON-PRESSURE RETAINING STRUCTURAL WELDING STANDARD (BASEPLATES OR SUPPORTS) :		
12		STANDARD FOR MAGNETIC PARTICLE OR LIQUID PENETRANT EXAMINATION (PLATE EDGES):		
13		STANDARD FOR POSTWELD HEAT TREATMENT :		
14		STANDARD FOR POSTWELD HEAT TREATMENT OF CASING FABRICATION WELDS :		
15		MATERIAL INSPECTION		
16		<b>THESE REFERENCES MUST BE LISTED BY THE PURCHASER</b>		
17		DEFAULT TO TABLE 14 (8.2.2.1)	YES	TABLE 14 INSPECTION CLASS: III
18		ALTERNATIVE MATERIAL INSPECTIONS AND ACCEPTANCE CRITERIA (SEE TABLE 15) (8.2.2.5)		
19		TYPE OF INSPECTION	METHOD	FOR FABRICATIONS
20		RADIOGRAPHY		
21		ULTRASONIC INSPECTION		
22		MAGNETIC PARTICLE INSPECTION		
23		LIQUID PENETRANT INSPECTION		
24		VISUAL INSPECTION (all surfaces)		
25	NOTES :			
26	1. Vendor shall complete this Datasheet and validate/verify/complete all materials, dimensions and sizes against the fluid characteristics. It shall be submitted as part of the Vendor bid.			
27	2. This data sheet shall be read in conjunction with the PID (CMIT-240048-728-PCS-15.11-0016) . The Pump Scope of Supply shall be as specified (battery limits) in the relevant PID.			
28	3. For Detailed Medium Properties information, please refer to the Material and Heat Mass Balance PFD (CMIT-240048-728-PCS-15.01-0002).			
29	4. The pump (including motor and auxiliaries (excluding mechanical seal, wear rings, shaft sleeve, gasket, shim and O-rings)) shall be designed and constructed for a minimum service life of 25 years and at least 3 years of continuous (uninterrupted) operation.			
30	5. The Preferred Operating Region shall be within 70% to 120% of Pump's BE Flow-rate. The Rated Flow shall be within the region of 80% to 110% of the Pump's Best Efficiency Flow-rate as furnished.			
31	6. For Parallel operation, Head Rise from Rated Point to Shut-off shall be ≥10%.			
32	7. The Vendor shall furnish the Performance Curve for the Pumps with the Duty Point, Power Absorbed, Efficiency, and NPSH Required marked along with the Bid.			
33	Moreover, the Vendor shall provide a similar and discrete Performance Curve for numerous pumps' operation modes (parallel or series).			
34	8. The Casing and Impeller types shall be selected by the Vendor based on the Fluid Properties and the targeted Operating and Design Parameters.			
35	9. The Vendor shall select and confirm the Mechanical Seal Type and Flushing Plan suitable for the Pumping Fluid to comply with API 682-specific requirements.			
36	10. All necessary Power/Control Panels, Instruments, Cabling, and Junction Boxes shall be supplied by the Vendor.			
37	11. The Pump's Coating shall meet the requirements of Local Ambient Conditions such as Ultraviolet Radiation and Sandstorm. The Vendor shall select a Coating of high quality.			
38	12. The Baseplate Rim/Pan shall be sloped at least 1:120 toward the Pump's End and equipped with a Tapped Drain Opening ≥ 2 NPS.			
39	13. The Baseplate shall be extended under the Pump, Drive Train Components, all Pipe Joints, and Pipe Flange Faces (including Pump Suction and Discharge Flanges) where all shall be within the Drain Pan/Rim Collection Area.			
40	14. Mounting Pads shall be provided for the Pump and all Drive Train Components.			
41	15. The Baseplate shall be equipped with Lifting Lugs for at least a four-point lift. Lifting the Baseplate, complete with all equipment mounted, shall not permanently distort or otherwise damage the Baseplate or the Machinery mounted on it.			
42	16. The Vendor (Manufacturer) shall guarantee the material of the Pump can meet the requirements for anticorrosion following API610/MR0175. All Pump Materials (including the Coupling Guard) shall be Non-Spark.			
43	17. As a minimum, 1m shall be kept as NPSH Margin (difference between the NPSH3 and the determined NPSH <sub>d</sub> ). The NPSH3, specified by the Vendor, shall be based on water (at a Temperature <55 °C) at Rated Flow and Rated head.			
44	18. The Rated Impeller Diameter shall be ≤ 95% of the Maximum Impeller Size possible for the Pump's Casing.			
45	19. All Shafts shall be of Forged Material. Rotors/Coupling shall dynamically be balanced to ISO G2.5 quality.			
46	20. Auxiliary Connections to the Pressure Casing, except the Seal Gland, shall be Socket-Welded, Butt-Welded, or Integrally-Flanged.			
47	21. Design and Supply of the Anchor Bolts and Levelling Screws shall be in the Vendor's Scope of Supply.			
48	22. The Bolts/Nuts shall be coated with Anti-Rust Approved Materials. The Bolts/Nuts for Internal Parts shall be of Anti-Corrosive Materials. The Bolting for Pressure Casings shall conform to API 610-specific requirements.			
49	23. The Pump Shut-off Pressure at the Rated Impeller Diameter shall not exceed the downstream System Design Pressure considering Maximum Suction Pressure, Maximum Density, Operation up to Trip Speed, and all applicable tolerances.			
50	24. All Pressure Parts shall be provided with Material Certificates conforming to BS EN10204-type 3.1.			
51	25. All fabricated joints in the Seal System Piping shall be Full Penetration Butt Welded and the Weld Root shall be made by GTAW Welding.			
52				
53				
54				
55				
56				
57				
58				
59				
60				
61				
62				
63				
64				



## DATA SHEET FOR BOOSTER PUMP (P-282221A/B/C)

Owner Doc.No.	CMIT-240048-728-ROT-15.17-0001	
Job's Doc. No.	253001D0728ME00D01	
Phase	Detailed Design	
Rev	C	Page 7 of 7

1	Note	Rev
2	26. Noise Level (Sound Pressure Level (Lp)) shall be ≤85dBA @ 1m distance from the Equipment's (Driver + Driven Equipment Train) surface at all directions. Acoustic hoods shall be provided, if necessary to meet the Noise Level's requirements.	
3	27. The number of Vibration Probes and Temperature Detectors requirements will depend on the Equipment and the selected Bearings as it shall be finalized by the Vendor. The Monitors with the Connecting Cables to the Probes and Detectors shall be supplied by the Vendor per API670.	
4	28. Suction/Discharge Mating Flanges' along with Bolts/Nuts and Gasket to be supplied by the Vendor.	
5	29. The Vendor shall supply all Tools, Accessories, and Consumables required for the Skid Installation, Commissioning, Test-run, and 3 months of Operation. Also, the Vendor shall supply the Commissioning and 2-Year Spare Parts.	
6	30. All required Interconnecting Piping and Cabling between the Main Pump Skid and accessory Equipment Skids shall be supplied by the Pump's Vendor.	
7	31. All Witnessed Inspections and Tests are Hold Points. Purchaser prefer not to have Preliminary Tests prior to Witnessed Tests to understand any difficulties encountered during testing.	
8	32. The need for the Casing Disassembly after the Final Performance Test shall be judged by the Vendor or if any abnormal observations existed during the Test.	
9	33. Hardness Test of Parts, Welds, and Heat Affected Zones shall be performed by the Vendor.	
10	34. 100% Dye Penetration Test and 100% Radiographic Examination shall be performed for all Butt-Welded Joints.	
11	35. A Minimum of 3mm shall be considered as Corrosion Allowance for the Pump's Casing. However, the Vendor is allowed to propose an alternative CA value, including zero value, provided that the selected Material of Construction fulfills the service life requirements set in point (4) above and without affecting the pump's safety or reliability.	
12		
13		
14		
15		
16		
17		
18		
19		
20		
21		
22		
23		
24		
25		
26		
27		
28		
29		
30		
31		
32		
33		
34		
35		
36		
37		
38		
39		
40		
41		
42		
43		
44		
45		
46		
47		
48		
49		
50		
51		
52		
53		
54		
55		
56		
57		
58		
59		
60		
61		
62		
63		
64		